


		HWA Variante liegend							HWA Variante stehend			
Pumpenanlage		SK-32/2				SK-32/3			SK-32/2		SK-32/3	
Kesselgröße		60 l	100 l	150 l	300 l	100 l	150 l	300 l	150 l	300 l	150 l	300 l
Fördermenge	m ³ /h	1,8 - 4				2,3 - 4			1,8 - 4		2,3 - 4	
Förderhöhe _{max}	m	38				50			38		50	
Nullförderhöhe _{Q=0}	m	60				90			60		90	
Saughöhe	m	7				7			7		7	
Motorleistung	kW	1,1				1,5			1,1		1,5	
Nennspannung	V	230; 230/400				230; 230/400			230; 230/400		230; 230/400	
Frequenz	Hz	50				50			50		50	
Fördermediumtemperatur _{max}	°C	50				50			50		50	
Masse Anlage	kg	67	78	85	113	80	87	115	85	113	87	115



Maße						
Baugr.	60*	100*	150	150 st.	300	300 st.
l	820	950	1230	-	1490	-
b	380	450	450	450	550	550
h1	770	830	820	1200	910	1550
h2	220	240	130	375	85	400
NW _S	R1 ^{1/4"}	R1 ^{1/4"}	R1 ^{1/4"}	R1 ^{1/4"}	R1 ^{1/4"}	R1 ^{1/4"}
NW _D	R1"	R1"	R1"	R1 ^{1/4"}	R1"	R1 ^{1/4"}

* Maße gelten für Druckkessel mit auswechselbarer Membran; Maße für andere Druckkessel auf Anfrage

